PoE Unmanaged Switch

ALSTRON™

Model	ALP-04100	ALP-08100	ALP-08100-2
			
PoE			
PoE Standard	IEEE802.3af, IEEE802.3at, IEEE802.3at+ (Mode A)		
PoE Distance	100m		
Chipset	IC+ (Ethernet), Maxim (PoE), Texas Instrument (Power)		
Interface			
Ethernet Ports	4 x 10/100 Base-TX PoE Ports 1 x 10/100 Base-TX Uplink Port AUTO Negotiation/ AUTO MDI/MDIX Full-duplex	8 x 10/100 Base-TX PoE Ports 1 x 10/100 Base-TX Uplink Port AUTO Negotiation/ AUTO MDI/MDIX Full-duplex	8 x 10/100 Base-TX PoE Ports 2 x 10/100 Base-TX Uplink Port AUTO Negotiation/ AUTO MDI/MDIX Full-duplex
LED Indicators	System: Power, PoE, Port: Link, Activity		
System			
Switching Capacity	1G (1K MAC Address)	1.8G (1K MAC Address)	
Power			
Input	AC 100 ~ 240V, 50/60Hz DC 48V Output (Power Adaptor)		
Power Consumption	65W (62W for PoE)	125W (123W for PoE)	
Mechanical			
Dimension (L x W x H)	119 x 85 x 28 mm (Metal Case)	218 x 107 x 29 mm (Metal Case)	
Weight	0.95 kg	1.6 kg	
Environmental			
Operating Temperature	-10 ~ 45 ºC (Fanless Design)		
Operating Humidity	10 ~ 85% (non-condensing)		

	15.4W per Port	25.5W per Port	30W per Port
ALP-04100	4	2	-
ALP-08100	8	4	-
ALP-08100-2	8	4	-

Related Products



PoE Extender
ALP-X025
ALP-X025G



PoE Lightning Surge Protector
ALP-SP1000



Unmanaged Gigabit Switch
ALP-16100U-SW
ALP-24100U-SW



Media converter
EF24-1G-1Fm-SC-550M
EF24-1G-1Fs-SC-10
EF24-1G-1SFP

Surveillance, Communication and Power Solutioning Products Specialist

www.poe.com.sg sales.sg@alstron.com.sg

** Product specifications and model are right at the point of catalog publication. It is subjected to change without advance notice.*