

Model	ALP-FCH-G-SFP-30	ALP-FCH-G-SFP-60
		
PoE		
PoE Standard	IEEE802.3af, IEEE802.3at (Mode A)	IEEE802.3af, IEEE802.3at, IEEE802.3at+ (Mode A)
PoE Distance	100m	
Chipset	Marvell (Ethernet), Microsemi (PoE), Linear (Power)	
Interface		
Ethernet Ports	1 x 10/100/1000 Base-TX RJ45 Port (PoE), (AUTO Negotiation / AUTO MDI/MDIX) 1 x 1000M SFP	
LED Indicators	Power Indicators (Green LED x 2) RJ45 Port Link/ACT (Green), Duplex/Collision (Amber), SFP Port Link/ACT (Green)	
Power		
Input	DC 48V ~ 56 V (Depend on Adaptor)	
Power Consumption	2 W (no PoE Load)	2 W (no PoE Load)
PoE Output	30W (Max)	60W (Max)
Mechanical		
Dimension (L x W x H)	32 x 81.5 x 103 mm	
Weight	140 g	
Environmental		
Operating Temperature	-40 ~ 75 °C (Fanless Design)	
Operating Humidity	5% ~ 95% (non-condensing)	

Related Products



Power Adaptor
CSE4820-2
CSE4830-2



Din-Rail Mount PSU
DR-75-48
DR-120-48
DRP-240-48



SFP
ALP-SFP-G-LC-05
ALP-SFP-G-LC-2
ALP-SFP-G-LC-10
ALP-SFP-G-LC-30



L3 Managed SFP & SFP+ Switch
ALP-SFP-G-12-SW
ALP-SFP-G-24-SW