

Model	ALP-08100U-SW
Brand	Alstron
	
Distance	100 m
Interface	
Ethernet Ports	8 x 10/100/1000 Mbps RJ45 Ports AUTO Negotiation / AUTO MDI/MDIX Full-duplex
LED Indicators	System: Power, Port: Link, Activity
System	
Switching Capacity	16 Gbps (4K MAC Address)
Forwarding Rate	11.9 Million PPS
Power	
Power Input	AC 100 ~ 240V, 50/60Hz, DC 12V 1A (Power Adaptor)
Power Consumption	≤ 5.76 Watts
MTBF	> 50,000 (@25 °C)
Mechanical	
Dimension (L x W x H)	138 x 78 x 25 mm (Metal Case)
Nett Weight	Approx. 0.4 kg
Environmental	
Standards	Design comply to CE, EMC Class A
Storage Temperature	-10 ~ 50 °C
Operating Temperature	0 ~ 40 °C (Fanless Design)
Operating Humidity	5% ~ 95% (non-condensing)

Related Products



Managed Gigabit PoE Switch
ALP-16100G-250
ALP-24100G-370



L2 Managed Gigabit Switch
ALP-24100G-SW-L2

* Product specifications and model are right at the point of catalog publication. It is subjected to change without advance notice.