

Model	ALP-FCN-G-SC-05	ALP-FCN-G-SC-20	ALP-FCN-G-SFP
Brand	Alstron		
	and and a second	all	minut,
Interface			
Port	1 RJ45 + 1 Fiber Port		1 RJ45 + 1 SFP Port
Ethernet Port	10/100/1000 Mbps RJ45 Port Auto MDI/MDI-X, Auto Negotiation		
Fiber Port	1000 BaseFX (SC Connector)		SFP Slot
Media Type	Multi Mode	Single Mode	SFP Based
Distance	0.55 km	20 km	SFP Based
Bit Rate	1250 Mbps		
Wavelength	850 nm	1310 nm	SFP Based
TX Power	-4 ~ -9.5 dBm	-3 ~ -9.5 dBm	SFP Based
RX	< -18	< -20	SFP Based
Power			
Power Input	DC 5 V 2 A (Power Adaptor)		
Power Consumption	≤ 6 Watts		
Mechanical			
Dimension (L x W x H)	110 x 70 x 25mm		
Weight	0.39 kg		
Environmental			
Storage Temperature	-10 ~ 50 °C		
Operating Temperature	-10 ~ 40 °C		
Operating Humidity	10 ~ 85% (non-condensing)		

Related Products







Rack Mounted Media
Converter Chasis
ALP-2URMC-14-AC

25

Surveillance, Communication and Power Solutioning Products Specialist

www.poe.com.sg

sales.sg@alstron.com.sg



Model	ALP-FCN-G-SFP	ALP-FCN-G-SFP-P30	
Brand	Alstron		
Interface			
Port	1 RJ45 + 1 SFP Port	1 RJ45 (POE) + 1 SFP Port	
Ethernet Port	10/100/1000 Mbps RJ45 Port Auto MDI/MDI-X, Auto Negotiation		
PoE Budget	N/A	IEEE 802.at / 30W (Mode A)	
Fiber Port	SFP Slot		
Media Type	SFP Based		
Distance	SFP Based		
Bit Rate	1250 Mbps		
Wavelength	SFP Based		
TX Power (dBm)	SFP Based		
RX	SFP Based		
Power			
Input Voltage	DC 5 V 2 A (Power Adaptor)	AC100-240V (50/60Hz) Input Cable with UK Style Plug provided	
Mechanical			
Dimension (L x W x H)	110 x 70 x 25mm	140 x 110 x 40mm	
Weight	0.39 kg	0.56 kg	
Environmental			
Storage Temperature	-10 ~ 50 °C		
Operating Temperature	-10 ~ 40 °C		
Operating Humidity	10 ~ 85% (non-condensing)		

Related Products



SFP see page 28



Rack Mounted Media
Converter Chasis
ALP-2URMC-14-AC

26

Surveillance, Communication and Power Solutioning Products Specialist

www.poe.com.sg

sales.sg@alstron.com.sg



Model	ALP-FCN-SC-05	ALP-FCN-SC-20	
Brand	Alstron		
	The state of the s	The state of the s	
Interface			
Port	1 RJ45 + 1 Fiber Port		
Ethernet Port	10/100 Mbps RJ45, Auto MDI/MDI-X, Auto Negotiation		
Fiber Port	100 BaseFX (SC Connector)		
Media Type	Multi Mode	Single Mode	
Distance	0.55 km	20 km	
Bit Rate	155 Mbps		
Wavelength	850 nm	1310 nm	
TX Power	-14 ~ -20 dBm	-8 ~ -15 dBm	
RX	<-31	< -34	
Power			
Power Input	DC 5 V 1 A (Power Adaptor)		
Power Consumption	≤ 6 Watts		
Mechanical			
Dimension (L x W x H)	110 x 70 x 25mm		
Weight	0.39 kg		
Environmental			
Storage Temperature	-10 ~ 50 °C		
Operating Temperature	-10 ~ 40 °C		
Operating Humidity	10 ~ 85% (non-condensing)		

Related Products



SFP see page 28-35



Media converter ALP-FCN-G-SC-05 ALP-FCN-G-SC-20 ALP-FCN-G-SFP



Rack Mounted Media
Converter Chasis
ALP-2URMC-14-AC

24

Surveillance, Communication and Power Solutioning Products Specialist

www.poe.com.sg

sales.sg@alstron.com.sg