

<b>Model</b>	ALP-SP1000-E
<b>Brand</b>	Alstron
	
<b>System</b>	
<b>Interface Port</b>	RJ45
<b>Transmission Rate</b>	10 / 100 / 1000 Mbps
<b>Insertion Loss</b>	Network Signal : $\leq 0.2$ dB
<b>Protected Core</b>	Network Signal : 1~8 line
<b>Power</b>	
<b>Working Voltage</b>	Network Signal : 5 V
<b>Rated Current</b>	300 mA
<b>Impulse Voltage (10/700μs)</b>	C-X: 6 KV ; X-X (Data) : 2 KV
<b>Voltage Protection Level (Up)(10/700μs)</b>	C-X $\geq$ 500 V ; X-X(Data) $\leq$ 15 V
<b>Response Time</b>	$\leq 1$ ns
<b>Mechanical</b>	
<b>Dimension (L x W x H)</b>	112 x 38 x 30 mm
<b>Nett Weight</b>	Approx. 0.13 kg
<b>Environmental</b>	
<b>Standards</b>	Design comply to CE
<b>Storage Temperature</b>	-20 ~ 70 °C
<b>Operating Temperature</b>	-20 ~ 60 °C
<b>Operating Humidity</b>	< 90% (non-condensing)