

Model	EDR-75-48	NDR-120-48	DRP-240-48
Brand	Meanwell		
			
System			
Safety Standard	UL, TUV		
Protection	Overload, Over Voltage, Over Temperature		
Power			
Input Voltage	AC 100 ~ 240V, 50/60Hz		
Output Voltage	DC 48 V 1.6 A (76.8 W)	DC 48 V 2.5 A (120 W)	DC 48 V 5 A (240 W)
Mechanical			
Dimension (L x W x H)	100 x 55.5 x 125.2 mm	100 x 65.5 x 125.2 mm	100 x 125.5 x 125.2 mm
Weight	0.6 kg	0.79 kg	1.2 kg
Environmental			
Storage Temperature	-10 ~ 60 °C	-10 ~ 70 °C	-10 ~ 80 °C
Operating Temperature	0 ~ 50 °C	-10 ~ 60 °C	-10 ~ 70 °C
Operating Humidity	20% ~ 95% (non-condensing)		

Model	HDR-30-12	EDR-75-12	NDR-120-12
<b>Brand</b>	<b>Meanwell</b>		
			
<b>System</b>			
<b>Safety Standard</b>	UL, TUV		
<b>Protection</b>	Overload, Over Voltage	Overload, Over Voltage, Over Temperature	
<b>Power</b>			
<b>Input Voltage</b>	AC 100 ~ 240 V, 50/60 Hz		
<b>Output Voltage</b>	DC 12 V 2 A (24 W)	DC 12 V 6.3 A (75.6 W)	DC 12 V 10 A (120 W)
<b>Mechanical</b>			
<b>Dimension (L x W x H)</b>	56 x 78 x 93 mm	100 x 55.5 x 125.2 mm	100 x 65.5 x 125.2 mm
<b>Weight</b>	0.27 kg	0.6 kg	0.79 kg
<b>Environmental</b>			
<b>Storage Temperature</b>	-20 ~ 70 °C	-10 ~ 70 °C	
<b>Operating Temperature</b>	-20 ~ 60 °C	-10 ~ 60 °C	
<b>Operating Humidity</b>	20% ~ 95% (non-condensing)		