

Model	ALP-08100-2	ALP-08100G-2
		
PoE		
PoE Standard	IEEE802.3af, IEEE802.3at (Mode A)	
PoE Budget	120 Watts	120 Watts
Interface		
Ethernet Ports	8 x 10/100 Mbps RJ45 PoE Ports 2 x 10/100 Mbps RJ45 Uplink Port AUTO Negotiation / AUTO MDI/MDIX Full-duplex	8 x 10/100/1000 Mbps RJ45 PoE Ports 2 x 10/100/1000 Mbps RJ45 Uplink Port AUTO Negotiation / AUTO MDI/MDIX Full-duplex
LED Indicators	System: Power, PoE Port: Link, Activity	
System		
Switching Capacity	1.8G (4K MAC Address)	20G (4K MAC Address)
Power		
Power Input	AC 100 ~ 240V, 50/60Hz DC 48V Output (Power Adapter)	AC 100 ~ 240V, 50/60Hz
Mechanical		
Dimension (L x W x H)	218 x 107 x 29 mm (Metal Case)	200 x 118 x 44 mm (Metal Case)
Nett Weight	Approx. 1.1 kg	Approx. 1.1 kg
Environment		
Standards	Design comply to CE, EMC Class A	
Storage Temperature	0 ~ 50 °C	
Operating Temperature	0 ~ 40 °C (Fanless Design)	
Operating Humidity	20 ~ 89% (non-condensing)	

Related Products



PoE Extender
ALP-X025
ALP-X025G



PoE Lightning Surge Protector
ALP-SP1000



L2 Managed Gigabit Switch
ALP-24100G-SW-L2



Media Converter
EF24L-1G-1Fm-SC-550M
EF24L-1G-1Fs-SC-10
EF24L-1G-1SFP

* Product specifications and model are right at the point of catalog publication. It is subjected to change without advance notice.