Gigabit PoE Injector



Model	ALP-I030-16	ALP-1030-24
Brand	Alstron	
PoE		
PoE Standard	IEEE802.3af IEEE802.3at (Mode A)	IEEE802.3af IEEE802.3at (Mode A)
PoE Budget	480 Watts	720 Watts
Interface		
Port	16 x 10/100/1000 Mbps RJ45 PoE Port 16 x 10/100/1000 Mbps RJ45 LAN Port	24 x 10/100/1000 Mbps RJ45 PoE Port 24 x 10/100/1000 Mbps RJ45 LAN Port
LED Indicators	System: AC Power, User Indicator: Channel Power	
Power		
Power Input	AC 100~240V, 50/60Hz	
PoE Output Power	DC 52V	
Power Consumption	≤ 500 Watts (With PoE)	≤ 1000 Watts (with PoE)
Mechanical		
Dimension (L x W x H)	440 x 350 x 45 mm	
Nett Weight	Approx. 4 kg	Approx. 4.6 kg
Environmental		
Standards	Design comply to CE	
Storage Temperature	-10 ~ 60 °C	
Operating Temperature	-10 ~ 50 °C	
Operating Humidity	Maximum 80%, Non-condensing	

Related Products



L2 Managed Gigabit Switch ALP-24100G-SW-L2









18

Surveillance, Communication and Power Solutioning Products Specialist

www.poe.com.sg

sales.sg@alstron.com.sg