Rugged PoE Media Converter



Model	ALP-FCH-G-SFP-60
Brand	Alstron
	To the second se
РоЕ	
PoE Standard	IEEE802.3af, IEEE802.3at, IEEE802.3at+ (Mode A)
PoE Budget	60 Watts
Interface	
Ethernet Ports	1 x 10/100/1000 Mbps RJ45 Port (PoE), (AUTO Negotiation / AUTO MDI/MDIX) 1 x Gigabit SFP
LED Indicators	Power Indicators (Green LED x 2) RJ45 Port Link/ACT (Green), Duplex/Collision (Amber), SFP Port Link/ACT (Green)
Power	
Power Input	DC 48V ~ 56 V (Depend on Power Supply Unit)
Power Consumption	≤ 2 Watts ≤ 62 Watts (with PoE)
MTBF	> 50,000 (@ 40 °C)
Mechanical	
Dimension (L x W x H)	32 x 81.5 x 103 mm
Nett Weight	Approx. 0.14 kg
Environmental	
Standards	Design comply to CE
Storage Temperature	-40 ~ 85 °C
Operating Temperature	-40 ~ 75 °C (Fanless Design)
Operating Humidity	5% ~ 95% (non-condensing)

Related Products



CSE4820-2 CSE4830-2



<u>SFP</u> see page 37



Managed SFP & SFP+ Switch
ALP-SFP-G-24-SW-L3
ALP-SFP-G-28-SW-L2

12

Surveillance, Communication and Power Solutioning Products Specialist

www.poe.com.sg

sales.sg@alstron.com.sg