

Model	ALP-FCN-G-SC-05	ALP-FCN-G-SC-20	ALP-FCN-G-SFP
Brand	Alstron		
			
Interface			
Port	1 RJ45 + 1 Fiber Port		1 RJ45 + 1 SFP Port
Ethernet Port	10/100/1000 Mbps RJ45 Port Auto MDI/MDI-X, Auto Negotiation		
Fiber Port	1000 BaseFX (SC Connector)		SFP Slot
Media Type	Multi Mode	Single Mode	SFP Based
Distance	0.55 km	20 km	SFP Based
Bit Rate	1250 Mbps		
Wavelength	850 nm	1310 nm	SFP Based
TX Power	-4 ~ -9.5 dBm	-3 ~ -9.5 dBm	SFP Based
RX	< -18	< -20	SFP Based
Power			
Power Input	DC 5 V 2 A (Power Adaptor)		
Power Consumption	≤ 6 Watts		
Mechanical			
Dimension (L x W x H)	110 x 70 x 25mm		
Nett Weight	Approx. 0.39 kg		
Environmental			
Standards	Design comply to CE		
Storage Temperature	-10 ~ 50 °C		
Operating Temperature	-10 ~ 40 °C		
Operating Humidity	10 ~ 85% (non-condensing)		

Related Products



SFP
see page 37



Managed SFP & SFP+ Switch
ALP-SFP-G-24-SW-L3
ALP-SFP-G-28-SW-L2